

842 HYDR



M515



1000A6





1000S6



1600 SUPER



BLOCCHIERE MOBILI- EGG-LAYING BLOCK MACHINES - MACHINES A BLOCS PONDEUSES

	842Hydr - M515	1000A6	1000S6	1600Super
Produzione oraria blocchi Production per hour blocks Production horaire parpaings (cm 20x40xh20) 	200-300	300-400	500-700	750-1000
Prod. Oraria pavé - Cordoli Prod. Per hour pavers-kerbstones Prod. Horaire pavé - Bordures 	no	no	Pavé no Cordoli/kerbstones /bordures:160-240	no
Numero blocchi per sfornata Blocks per mould Parpaings chaque moule (in cm)	10x40xh20=7 15x40xh20=5 20x40xh20=4	10x40xh20=12 15x40xh20=8 20x40xh20=6	10x40xh20=12 15x40xh20=8 20x40xh20=6	10x40xh20=12 15x40xh20=8 20x40xh20=6
Cicli/ora - Cycles/hour - Cycles /heure	50-75	50-65	80-120	125-165
Dimensione massima stampo - Maximum mould size Dimension maximale moule	Cm 80x40xh20	126x45xh20	126x45xh20	126x45xh20
Altezza massima blocco Maximum block height Hauteur maximale parpaing	Cm 20	Standard cm 20 max cm 25 special cm 30	Standard cm 20 max cm 25 special cm 30	Standard cm 20 special cm 22,5
Altezza minima stampo - Minimum mould height Hauteur minimale moule	Cm 20	Cm 20	Cm 20	Cm 20
Capacità tramoggia/ Hopper capacity/ Capacité tremie	no	no	500 lt	650 lt
Motori - Motors - Moteurs	3 mot.	4 mot.	4 mot.	4 mot.
Potenza installata/ Installed power puissance installée	4,3Hp (3,2kW)	8,2Hp (6kW)	8,6Hp (6,3 kW)	9,1Hp (6,7kW)
Equipaggiamento sussidiario Ancillary equipment Dotation subsidiaire	Betoniera inv./ Reverse charge mixer/Bétonniere 400lt + Carriola/wheelbarrow/ brouette	Betoniera/ Reverse charge mixer/Bétonniere 750lt + Carriola/wheelbarrow/ brouette	Mesc.plan./plan Mix./malax.plan. 500lt + Dumper 1.5m	Mesc.plan./plan Mix./malax.plan. 500lt + Dumper 1.5m